

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	Knauf Insulation
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-KIN-20150185-CBB2-EN
ECO EPD Ref. No.	ECO-00000242
Issue date	17.08.2015
Valid to	16.08.2020

**FKD-T / FKD-T C1 / FKD-T C2 / FKD-U C2 / FKD-S /
FKD-S C1 / FKD-S C2 / FKD-S Thermal / FKD-N / FKD-N
C1 / FKD-N C2 / FKD-N Thermal / SMARTwall N C1 /
SMARTwall N C2 /
SMARTwall S C1 / SMARTwall S C2 /
OUT-Therm / OUT-Therm C1 / OUT-Therm C2
Rock Mineral Wool for ETICS
(External Thermal Insulation Composite Systems)
Knauf Insulation**

www.bau-umwelt.com / <https://epd-online.com>



General Information

Knauf Insulation

Programme holder

IBU - Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Declaration number

EPD-KIN-20150185-CBB2-EN

This Declaration is based on the Product Category Rules:

Mineral insulating materials, 07.2014
(PCR tested and approved by the SVR)

Issue date

17.08.2015

Valid to

16.08.2020



Prof. Dr.-Ing. Horst J. Bossenmayer
(President of Institut Bauen und Umwelt e.V.)



Dr. Burkhard Lehmann
(Managing Director IBU)

FKD-T / FKD-T C1 / FKD-T C2 / FKD-U C2 / FKD-S / FKD-S C1 / FKD-S C2 / FKD-S Thermal / FKD-N / FKD-N C1 / FKD-N C2 / FKD-N Thermal / SMARTwall N C1 / SMARTwall N C2 / SMARTwall S C1 / SMARTwall S C2 / OUT-Therm / OUT-Therm C1 / OUT-Therm C2

Owner of the Declaration

Knauf Insulation
rue E. Franqui, 7
1435 Mont-Saint-Guibert
Belgium

Declared product / Declared unit

1 m³ of product

Scope:


The declared unit is 1 m³ FKD-T / FKD-T C1 / FKD-T C2 / FKD-U C2 / FKD-S / FKD-S C1 / FKD-S C2 / FKD-S Thermal / FKD-N / FKD-N C1 / FKD-N C2 / FKD-N Thermal / SMARTwall N C1 / SMARTwall N C2 / SMARTwall S C1 / SMARTwall S C2 / OUT-Therm / OUT-Therm C1 / OUT-Therm C2 rock mineral wool uncoated, one side coated or both sides coated. They comply with the requirements of /EN 13162/. The thickness is ranging from 40 mm to 300 mm. The manufacturing company is Knauf Insulation - plants Sankt Egidien (Germany) and Nova Bana (Slovakia) - with averages following production share. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Norm /EN 15804/ serves as the core PCR

Independent verification of the declaration
according to /ISO 14025/

☐ internally ☒ externally



Matthias Schulz
(Independent verifier appointed by SVR)

Product

Product description

Knauf Insulation manufactures rock mineral wool (RMW) insulation products. They are available in the form of lamellas, slabs or boards, and also possibly rolls. The density range for RMW goes from 25 to 200 kg/m³. In terms of composition, inorganic rocks are the main components (typically 97%) of RMW, with a remaining fraction of organic content which is generally a thermosetting resin binder. The binder content is typically less than 4%. The inorganic part is made of volcanic rocks, typically basalt, also dolomite and with an increasing proportion of recycled material

in form of briquettes, a mix of stone wool scrap and cement.

RMW slabs are used as a thermal, acoustical and fire insulation product. They are produced with an uncoated, one side coated or both sides coated surface. This EPD has been developed for a double side coated product, this is the worst case scenario in terms of environmental impacts.

For the placing on the construction products market in the European Union/EFTA (with exception of Switzerland), the Regulation /(EU) No 305/2011/

applies. The products need Declarations of Performance / DoP R4308LPCPR / DoP R4308MPCPR / DoP R4308KPCPR / DoP R4238LPCPR / R4238MPCPR / R4238KPCPR / taking into consideration the harmonized product standard /EN 13162/ and the /CE-mark/.

Application

Main applications for the RMW slabs are: ETICS (External Thermal Insulation Composite Systems). For the application and use national regulations apply, in Germany the *Allgemeine bauaufsichtliche Zulassung Z-33.4-1351 / Z-33.4-1395 (building inspection approval) issued by the Deutsches Institut für Bautechnik (DIBt), Berlin.*

Technical Data

The FKD-T / FKD-T C1 / FKD-T C2 / FKD-U C2 / FKD-S / FKD-S C1 / FKD-S C2 / FKD-S Thermal / FKD-N / FKD-N C1 / FKD-N C2 / FKD-N Thermal / SMARTwall N C1 / SMARTwall N C2 / SMARTwall S C1 / SMARTwall S C2 / OUT-Therm / OUT-Therm C1 / OUT-Therm C2 slabs and its technical characteristics meet a number of technical requirements. The most important ones are summarized in the table here below, which also includes references to testing methods.

Technical characteristics

Name	Value	Unit
Water vapour diffusion resistance factor /SIST EN 13162/	1	-
Gross density /DIN 1602/	90 - 110	kg/m ³
Water absorption Wp /EN 1609/	< 1	kg/m ²
Water absorption Wlp /EN 12087/	< 3	kg/m ²
Reaction to fire /EN 13501-1/	Euroclass A1	-
Specific heat capacity /EN ISO 10456/	1030	J/kgK
Melting point /DIN 4102 / T17/	> 1000	°C
Specific heat capacity /EN ISO 10456	1030	J/kgK
Compressive stress FKD-T /EN 826/	10	kPa
Thermal conductivity FKD-T / FKD-N Thermal / SMARTwall N /EN 12667/	0.034	W/(mK)

Thermal conductivity FKD-U / FKD-N / FKD-S Thermal / SMARTwall S / OUT-Therm /EN 12667/	0.035	W/(mK)
Thermal conductivity FKD-S /EN 12667/	0.036	W/(mK)
Compressive stress FKD-S / FKD-S Thermal /SMARTwall S /EN 826/	30	kPa
Compressive stress FKD-U / FKD-N / FKD-N Thermal /EN 826/	20	kPa
Compressive stress SMARTwall N / OUT-Therm /EN 826/	25	kPa
Tensile strength FKD-T /EN 1607/	5	kPa
Tensile strength FKD-U / FKD-N / FKD-N Thermal / SMARTwall N / OUT-Therm /EN 1607/	7.5	kPa
Tensile strength FKD-S / FKD-S Thermal / SMARTwall S /EN 1607/	10	kPa
Acoustic absorption	not relevant	

Base materials / Ancillary materials

The main raw materials are diabase (a rock that is similar to volcanic rock basalt), dolomite and briquette. The briquette is made of rock mineral wool waste (internal or external), waste of raw materials and cement. Additionally, coke is also added in the cupola as an energy carrier. Further down the manufacturing line, a binder (thermo set resin) is spread onto the fibers. Then, the polymerization contributes to fix the products dimensions and mechanical properties. After cutting, the slabs are sprayed with a mineral silicate coating on the surface.

Reference service life

When used correctly, the reference service life of Knauf Insulation rock mineral wool is merely limited by the service life of the components and/or building in which it is incorporated; this is substantiated by current industry findings, for example in case of deconstruction of buildings. As a minimum, we consider a reference service life of 50 years.

LCA: Calculation rules

Declared Unit

The declared unit is 1 m³ of rock mineral wool both sides coated. The density used for the calculation of the LCA is 100 kg/m³.

Declared unit

Name	Value	Unit
Declared unit	1	m ³
Gross density	100	kg/m ³
Conversion factor to 1 kg	0.01	-

System boundary

The system boundary of the EPD follows the modular approach defined by /EN 15804/.

The type of EPD is cradle-to-gate-with options.

List and explanation of the modules declared in the EPD.

The product stage (A1-A3) includes:

- A1 - raw material extraction and processing, processing of secondary material input (e.g. recycling processes),
- A2 - transport to the manufacturer
- A3 - manufacturing.

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of waste state or disposal of final residues during the product stage. The LCA results are given in an aggregated form for the product stage, meaning that the modules A1, A2 and A3 are considered as **a unique module A1-A3.**

The construction process stage includes:

- A4 - transport to the construction site and
- A5 - installation into the building.

The transport to the building site (A4) is included in the LCA calculation. For the considered product, the average transport distance is assumed to be 500 km with a truck capacity utilization of 40%.

Module A5 has neither been included nor declared in this EPD, since it depends on the application, and method or tools used, which can be very diverse as a multi-purpose product. Therefore, the treatment of the packaging waste after the installation of the product has not been considered.

The use stage

Because they are specific to the building, its use and location, none of the modules related to the building fabric (B1-B5) nor the operation of the building (B6 and B7) have been taken into account in this EPD.

The end-of-life stage includes:

- C1 - de-construction, demolition,
- C2 - transport to waste processing,
- C3 - waste processing for reuse, recovery and/or recycling and
- C4 - disposal.

This includes provision of all transports, materials, products and related energy and water use, but only modules C2 and C4 are reported, as they are considered the most relevant scenarios for rock mineral wool products.

Although rock mineral wool products from Knauf Insulation are partly recycled at end-of-life, there is not yet an established collection system, and as such, the assumption chosen in this study, 100% landfilled after the use phase, is the most conservative approach.

Module D includes reuse, recovery and/or recycling potentials.

According to /EN 15804/, any declared benefits and loads from net flows leaving the product system not allocated as co-products and having passed the end-of-waste state shall be included in module D.

No benefits and loads are considered: module D is not included in the background model.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following information forms the basis for declared modules or can be used for specific scenarios development in building assessment context.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0025	l/100km
Transport distance	500	km
Capacity utilisation (including empty runs)	40	%
Gross density of products transported	100	kg/m ³

Reference service life

Name	Value	Unit
Reference service life	50	a

End-of-life (C1 - C4)

Name	Value	Unit
Landfilling	100	kg
Transport distance	50	km
Capacity utilization	50	%

LCA: Results

Environmental impacts associated with losses from installation of the product in A5 are not included in the LCA results. This is due to the fact that installation losses vary depending on installation practice and building project specifics. In order to include the potential environmental impacts associated with installation losses, a factor can be applied to the LCA results. E.g. installation losses = 1%, multiplication of EPD results with 1.01.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	MND	X	MND

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 m³ FKD-T/FKD-U/FKD-S/FKD-N/SMARTwall/OUT-Therm

Parameter	Unit	A1-A3	A4	C2	C4
Global warming potential	[kg CO ₂ -Eq.]	112.00	5.29	0.36	1.41
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	2.13E-9	2.53E-11	1.73E-12	1.92E-11
Acidification potential of land and water	[kg SO ₂ -Eq.]	1.25E+0	1.60E-2	2.38E-3	8.99E-3
Eutrophication potential	[kg (PO ₄) ³ -Eq.]	5.96E-2	3.38E-3	5.69E-4	1.23E-3
Formation potential of tropospheric ozone photochemical oxidants	[kg ethene-Eq.]	6.81E-2	-4.51E-3	-9.53E-4	8.44E-4
Abiotic depletion potential for non-fossil resources	[kg Sb-Eq.]	6.95E-5	1.99E-7	1.36E-8	5.30E-7
Abiotic depletion potential for fossil resources	[MJ]	1750.00	73.00	4.99	18.60

RESULTS OF THE LCA - RESOURCE USE: 1 m³ FKD-T/FKD-U/FKD-S/FKD-N/SMARTwall/OUT-Therm

Parameter	Unit	A1-A3	A4	C2	C4
Renewable primary energy as energy carrier	[MJ]	277.00	-	-	-
Renewable primary energy resources as material utilization	[MJ]	0.00	-	-	-
Total use of renewable primary energy resources	[MJ]	277.00	2.88	0.20	1.60
Non-renewable primary energy as energy carrier	[MJ]	1.71E+3	-	-	-
Non-renewable primary energy as material utilization	[MJ]	159.00	-	-	-
Total use of non-renewable primary energy resources	[MJ]	1.87E+3	7.32E+1	5.00E+0	1.94E+1
Use of secondary material	[kg]	13.00	-	-	-
Use of renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00
Use of non-renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00
Use of net fresh water	[m ³]	4.37E-1	2.03E-3	1.39E-4	-7.41E-2

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1 m³ FKD-T/FKD-U/FKD-S/FKD-N/SMARTwall/OUT-Therm

Parameter	Unit	A1-A3	A4	C2	C4
Hazardous waste disposed	[kg]	1.03E-1	1.67E-4	1.14E-5	8.72E-4
Non-hazardous waste disposed	[kg]	1.94E+1	9.21E-3	6.29E-4	1.04E+2
Radioactive waste disposed	[kg]	4.48E-2	9.59E-5	6.55E-6	3.39E-4
Components for re-use	[kg]	-	-	-	-
Materials for recycling	[kg]	-	-	-	-
Materials for energy recovery	[kg]	-	-	-	-
Exported electrical energy	[MJ]	-	-	-	-
Exported thermal energy	[MJ]	-	-	-	-

INTERPRETATION

RESOURCES USE

The primary energy demand from non-renewable resources is dominated by the production of rock mineral wool products (especially due to the energy carrier, coke) and the thermosetting resin binder. The renewable energy demand regarding the products FKD-T / FKD-T C1 / FKD-T C2 / FKD-U C2 / FKD-S / FKD-S C1 / FKD-S C2 / FKD-S Thermal / FKD-N / FKD-N C1 / FKD-N C2 / FKD-N Thermal / SMARTwall N C1 / SMARTwall N C2 / SMARTwall S C1 / SMARTwall S C2 / OUT-Therm / OUT-Therm C1 / OUT-Therm C2 is dominated by the production, mostly due to electricity consumption, and packaging.

ENVIRONMENTAL IMPACT

Every impact category except the abiotic ADP elements is dominated by the production. This is due to the consumption of energy (electricity and thermal energy) during the production.

The **Abiotic Depletion Potential elements** (ADPe) are dominated by the coating production followed by the binder production and by the supply of raw materials such as cement for briquettes.

The **Global Warming Potential (GWP)** is dominated by the production, mostly due to CO₂ emissions from raw materials and energy consumption. The production of the thermosetting resin binder represents more than 10% of the impact.

The **Ozone Depletion Potential (ODP)** is most notably influenced by the production and the binder.

The **Acidification Potential (AP)** is also dominated by the production due to the emissions related to the processes and the energy consumption. Mostly, the impact refers to emissions to air: 75% from sulphur dioxide and 20% from nitrogen oxides.

The **Eutrophication Potential (EP)** is significantly influenced by the production due to emissions from the cupola furnace, curing oven and other unit processes.

The **Potential Ozone Photochemical Oxidants (POCP)** is particularly dominated by the production (emissions in the cupola furnace and other unit processes). The results from the transport are negative due to the NO emissions; NO counteracts the POCP.

References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):
Generation of Environmental Product Declarations
(EPDs);

General principles

for the EPD range of Institut Bauen und Umwelt e.V.
(IBU), 2013/04
www.bau-umwelt.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and
declarations — Type III environmental declarations —
Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of
construction works — Environmental Product
Declarations — Core rules for the product category of
construction products

IBU 2013, PCR, Part A

PCR -Part A: Product Declarations of Institut Bauen
und Umwelt (IBU), Part A: Calculation Rules for the
Life Cycle Assessment and Requirements on the
Background Report. 2013/04

IBU 2014, PCR, Part B

PCR -Part B: Requirements on the EPD for Mineral
insulating materials (in German „Anforderungen an die
EPD für Mineralische Dämmstoffe“), Version 1.6
Institut Bauen und Umwelt e.V. 07/2014

GaBi 6 2012

GaBi 6: Software and database for life cycle
engineering. LBP, University of Stuttgart and PE
INTERNATIONAL AG, Leinfelden-Echterdingen, 2012.

GaBi 6 2012B

GaBi 6: Documentation of GaBi6-Datasets for life cycle
engineering. LBP University of Stuttgart and PE
INTERNATIONAL AG, 2012.

SoFi 6 2014

SoFi 6 database for Enterprise Sustainability
Performance. PE INTERNATIONAL AG, 2014

DIN 4108-10

DIN 4108-00 (2004-09): Thermal insulation and energy
economy in buildings - Part 10: Application-related
requirements for thermal insulation materials - Factory
made products

EN 13162

EN 13162:2012 Thermal insulation products for
buildings - Factory made MW products - Specification

EN 12667

EN 12667: 2001 Thermal performance of building
materials and products - Determination of thermal
resistance by means of guarded hot plate and heat
flow meter methods - Products of high and medium
thermal resistance

EN 1602

EN 1602: 2013 Thermal insulating products for building
applications - Determination of the apparent density

EN 1607

EN 1607: 2013 Determination of tensile strength
perpendicular to faces of Thermal Insulation Products

EN 29053

EN 29053: 1993 Acoustics; materials for acoustical
applications; determination of airflow resistance

EN 1609

EN 1609: 2013 Thermal insulating products for building
applications - Determination of short term water
absorption by partial immersion

EN 12087

EN 12087: 2013 Thermal insulating products for
building applications - Determination of long term water
absorption by immersion

EN 13501-1

EN 13501-1: 2009 Fire classification of construction
products and building elements - Part 1: Classification
using test data from reaction to fire tests

ISO 10456

ISO 10456: 2007 Building materials and products -
Hygrothermal properties - Tabulated design values and
procedures for determining declared and design
thermal values

DIN 4102 / T17

DIN 4102 / T17: 1990 Fire behaviour of building
materials and elements; determination of melting point
of mineral fibre insulating materials; concepts,
requirements and testing

Zulassung Z-33.4-1351 / Z-33.4-1395 [BF1]

Zulassung Z-33.4-1351 / Z-33.4-1395 [BF1]
Allgemeine bauaufsichtliche (building inspection

approval) issued by the Deutsches Institut für Bautechnik (DIBt), Berlin.

**DoP R4308LPCPR / R4308MPCPR / R4308KPCPR /
R4238LPCPR / R4238MPCPR / R4238KPCPR**
Declarations of Performance

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 - 3087748 - 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**Author of the Life Cycle Assessment**

Université de Liège
allée du 6 août B6
4000 Liège
Belgium

Tel +32 4 3663547
Fax +32 4 3663547
Mail saicha.gerbinet@ulg.ac.be
Web www.chimapp.ulg.ac.be



thinkstep

Thinkstep
Hauptstrasse 111
70771 Leinfelden-Echterdingen
Germany

Tel +49 (0)7113418170
Fax +49 (0)71134181725
Mail info@thinkstep.com
Web www.thinkstep.com

**Owner of the Declaration**

Knauf Insulation
rue E. Francqui 7
1435 Mont-Saint-Guibert
Belgium

Tel 003210488462
Fax 003210488474
Mail Jean-
Pierre.Pigeolet@knaufinsulation.com
Web www.knaufinsulation.com