

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	Knauf Insulation
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-KNA-20150022-CBB1-EN
Issue date	20.04.2015
Valid to	19.04.2020

Glass Mineral Blowing Wool for Cavity Wall Supafil Cavity Wall

Knauf Insulation

www.bau-umwelt.com / <https://epd-online.com>



General Information

Knauf Insulation

Programme holder

IBU - Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Declaration number

EPD-KNA-20150022-CBB1-EN

This Declaration is based on the Product Category Rules:

Mineral insulating materials, 07.2014
(PCR tested and approved by the SVR)

Issue date

20.04.2015

Valid to

19.04.2020



Prof. Dr.-Ing. Horst J. Bossenmayer
(President of Institut Bauen und Umwelt e.V.)



Dr. Burkhard Lehmann
(Managing Director IBU)

Supafil Cavity Wall

Owner of the Declaration

Knauf Insulation
rue E. Franqui, 7
1435 Mont-Saint-Guibert
Belgium

Declared product / Declared unit

1 m³ of Supafil Cavity Wall

Scope:


GM BW (Glass Mineral Blowing Wool) is a loose-fill, binder-free, factory made mineral wool insulation. It is manufactured in the form of flocks of unbounded virgin mineral wool and complies with the requirements of /EN 14064/. The manufacturing company is Knauf Insulation – plants Visé (Belgium) and Lannemezan (France). The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Norm /EN 15804/ serves as the core PCR

Independent verification of the declaration
according to /ISO 14025/

☐ internally ☒ externally



Matthias Schulz
(Independent verifier appointed by SVR)

Product

Product description

Knauf Insulation manufactures blowing wool insulation products. They are available in the form of loose-fill flocks, having a woolly consistency, compressed and packaged in bags. The target installed density for GM BW Cavity Wall and Timber Frame is 35 kg/m³. In terms of composition, GM BW consists of about ≥ 99% inert material. The inert part is made of recycled glass (external cullet, up to 80% of the composition), sand and limestone. The remaining fraction is made of organic hydrophobic, antistatic and anti-dust compounds. The additive content is typically about 0.5 % in weight.

GM BW is used as a thermal and acoustical insulation product. It is produced as a loose-fill product to be blown with a dedicated blowing machine and installation accessories. For the placing on the market of construction products in the European Union and EFTA (with the exception of Switzerland) /Regulation (EU) No 305/2011/ applies. The products need a Declaration of performance (DoP) taking into consideration the harmonized product standard /EN 14064/ and the /CE-mark/.

Application

Main applications for the GM BW are cavity walls, wood frame structures and light steel framing (walls,

partitions, floors and pitched roofs). For the application and use national regulations apply. In Germany, the Allgemeine bauaufsichtliche Zulassung Z-23.15-1461 (building inspection and application approval) issued by the Deutsches Institut für Bautechnik (DIBt) applies.

Technical Data

The GM BW and its technical characteristics meet a number of technical requirements. The most important ones are summarized in the table here below, which also includes references to testing methods.

Technical characteristics

Name	Value	Unit
Thermal conductivity /EN 12667/	0.034	W/(mK)
Water vapour diffusion resistance factor /EN 13162/	1	-
Water vapor diffusion equivalent air layer thickness	NA	m
Sound absorption coefficient	NA	%
Gross density /EN 1602/	30 - 40	kg/m³
Compressive strength	NA	N/mm²
Longit. air-diffusion resist. /EN 29053/	≥5	kNs/m⁴
Water absorption Wp /EN 1609/	< 1	kg/m²
Water absorption Wlp /EN 12087/	< 3	kg/m²
Reaction to fire /EN 13501-1/	A1	-

Specific heat capacity /EN ISO 10456/	850	J/kgK
Settlement /Annex K of EN 14064-1/	S1	

Base materials / Ancillary materials

GMW is an insulation material of mostly inorganic origin intended for thermal and acoustic insulation, as well as for fire prevention in construction and industry. Raw materials used in the production of GMW are

sand, limestone, soda ash and a high level of recycled glass (up to 80%).

Reference service life

The RSL or durability of GM BW is as long as the lifetime of the building in which it is used.

LCA: Calculation rules

Declared Unit

The declared unit is 1 m³ of GM BW. The density used for the calculation of the LCA is 35 kg/m³.

Declared unit

Name	Value	Unit
Declared unit	1	m ³
Gross density	35	kg/m ³
Conversion factor to 1 kg	0.0286	-

System boundary

The system boundary of the EPD follows the modular approach defined by /EN 15804/.

The type of EPD is cradle to gate - with options.

List and explanation of the modules declared in the EPD.

The product stage (A1-A3) includes:

- A1 - raw material extraction and processing, processing of secondary material input (e.g. recycling processes),
- A2 - transport to the manufacturer and
- A3 - manufacturing.

This includes provision of all materials, products and energy, packaging processing and their transport, as well as waste processing up to the end-of waste state or disposal of final residues during the product stage. The LCA results are given in an aggregated form for the product stage, meaning that the modules A1, A2 and A3 are considered as a unique module A1-A3.

The construction process stage includes:

- A4 - transport to the construction site and
- A5 - installation into the building.

The transport to the building site (A4) is included in the LCA calculation. For Supafil Cavity Wall, the average transport distance is assumed to be 600 km with a truck capacity utilization of 50%.

Module A5 has been included into this EPD as the blowing machine request electricity to blow the mineral wool into the cavity. The treatment of the packaging waste after the installation of the product has also been considered. The product losses during the construction process stage have not been directly taken into account into the LCA as this depends of the installer experience and represents very low impacts (less than 1%). If relevant, the losses can be taken into account by increasing the production impacts A1-A3 with the loss percentage and transfer this additional impact to A5.

The use stage.

Because they are specific for the building, its use and location, none of the modules related to the building

fabric (B1-B5) nor the operation of the building (B6 and B7) have been taken into account in this EPD.

The end-of-life stage includes:

- C1 - de-construction, demolition,
- C2 - transport to waste processing,
- C3 - waste processing for reuse, recovery and/or recycling and
- C4 - disposal.

This includes provision of all transports, materials, products and related energy and water use, but only modules C2 and C4 are reported, as they are considered the most relevant scenarios for glass mineral wool products.

Although glass mineral wool products from Knauf Insulation are partly recycled at end-of-life, there is not yet an established collection system and as such the assumption chosen in this study, 100% landfilled after the use phase, is the most conservative approach.

Module D includes re-use, recovery and/or recycling potentials.

According to /EN 15804/, any declared benefits and loads from net flows leaving the product system not allocated as co-products and having passed the end-of waste state shall be included in module D.

Benefits from packaging's incineration with energy recovery are considered in module D.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following technical information can be used for the development of specific scenarios in the context of a building assessment.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0577	l/100km
Transport distance	600	km
Capacity utilisation (including empty runs)	50	%
Gross density of products transported	35	kg/m ³

Installation into the building (A5)

Name	Value	Unit
Electricity consumption	0.004	kWh
Output substances following waste treatment on site (plastic and wooden packaging)	1.26	kg

Reference service life

Name	Value	Unit
Reference service life	50	a

End-of-life (C1 - C4)

Name	Value	Unit
Landfilling	35	kg
Transport distance	50	km
Capacity utilization	50	%

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement ¹⁾	Refurbishment ¹⁾	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	X	MND	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 m³ Supafil Cavity Wall

Parameter	Unit	A1-A3	A4	A5	C2	C4	D
Global warming potential	[kg CO ₂ -Eq.]	26.00	1.84	3.70	0.12	0.47	-1.67
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	3.84E-8	7.56E-12	1.97E-9	4.75E-13	7.83E-12	-4.61E-10
Acidification potential of land and water	[kg SO ₂ -Eq.]	9.69E-2	5.06E-3	3.40E-3	3.37E-4	2.93E-3	-3.80E-3
Eutrophication potential	[kg (PO ₄) ³⁻ -Eq.]	1.06E-2	1.26E-3	2.23E-4	8.39E-5	4.23E-4	-2.76E-4
Formation potential of tropospheric ozone photochemical oxidants	[kg Ethen Eq.]	6.77E-3	-1.46E-3	2.09E-4	-1.01E-4	2.84E-4	-3.45E-4
Abiotic depletion potential for non-fossil resources	[kg Sb Eq.]	2.28E-3	7.19E-8	1.17E-7	4.52E-9	1.68E-7	-1.38E-7
Abiotic depletion potential for fossil resources	[MJ]	393.00	25.30	7.38	1.59	6.20	-24.20

RESULTS OF THE LCA - RESOURCE USE: 1 m³ Supafil Cavity Wall

Parameter	Unit	A1-A3	A4	A5	C2	C4	D
Renewable primary energy as energy carrier	[MJ]	51.00	-	-	-	-	-
Renewable primary energy resources as material utilization	[MJ]	0.00	-	-	-	-	-
Total use of renewable primary energy resources	[MJ]	51.00	1.42	2.35	0.09	0.62	-2.33
Non-renewable primary energy as energy carrier	[MJ]	602.00	-	-	-	-	-
Non-renewable primary energy as material utilization	[MJ]	2.08	-	-	-	-	-
Total use of non-renewable primary energy resources	[MJ]	604.00	25.40	11.60	1.60	6.45	-28.40
Use of secondary material	[kg]	0.00	-	-	-	-	-
Use of renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00	0.00	0.00
Use of non-renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00	0.00	0.00
Use of net fresh water	[m ³]	1.58E-1	2.49E-3	9.25E-3	1.57E-4	1.19E-3	-4.71E-3

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1 m³ Supafil Cavity Wall

Parameter	Unit	A1-A3	A4	A5	C2	C4	D
Hazardous waste disposed	[kg]	4.33E-3	1.21E-5	5.49E-7	7.58E-7	2.04E-6	-7.07E-6
Non-hazardous waste disposed	[kg]	1.01E+0	3.62E-3	8.43E-3	2.27E-4	3.50E+1	-7.22E-3
Radioactive waste disposed	[kg]	8.34E-2	3.47E-5	1.68E-3	2.18E-6	9.87E-5	-1.65E-3
Components for re-use	[kg]	-	-	-	-	-	-
Materials for recycling	[kg]	-	-	-	-	-	-
Materials for energy recovery	[kg]	-	-	-	-	-	-
Exported electrical energy	[MJ]	-	-	-	-	0.00	0.00
Exported thermal energy	[MJ]	-	-	-	-	0.00	0.00

INTERPRETATION

USE OF RESOURCES

The primary energy from non-renewable resources is dominated by the production of glass mineral wool products (especially due to the energy consumption) and the packaging.

The renewable energy is dominated by the packaging (wood pallets) and the production (electricity mix).

ENVIRONMENTAL IMPACT

Every impacts category except the abiotic ADPe and ODP are dominated by the production. This is due to the consumption of energy (electricity and thermal energy) during the production of glass mineral wool products.

The **Abiotic Depletion Potential elements (ADPe)** are dominated by the raw material consumption.

The **Global Warming Potential (GWP)** is dominated by the production, mostly due to energy consumption (gas and electricity). The raw materials and transport to site also have a limited impact. GWP is reduced by the use of a high percentage of glass cullet (about 80%).

The **Ozone Depletion Potential (ODP)** is influenced by raw materials, production and packaging.

The **Acidification Potential (AP)** is also dominated by the production due to the emissions related to the processes and the energy consumption. Mostly, the impact refers to emissions to air: sulphur dioxide and nitrogen oxides.

The **Eutrophication Potential (EP)** is significantly influenced by the production due to emissions from the furnace and electricity consumption.

The **Potential Ozone Photochemical Oxidants (POCP)** is particularly dominated by the production (electricity consumption). The results from the transport are negative due to the NO emissions; NO counteracts the POCP.

References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):
Generation of Environmental Product Declarations
(EPDs);

General principles

for the EPD range of Institut Bauen und Umwelt e.V.
(IBU), 2013/04
www.bau-umwelt.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and
declarations — Type III environmental declarations —
Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of
construction works — Environmental Product
Declarations — Core rules for the product category of
construction products

IBU 2013 Part B

PCR -Part B: Requirements on the EPD for Mineral
insulating materials (in German „Anforderungen an die
EPD für Mineralische Dämmstoffe“), Version 1.3
Institut Bauen und Umwelt e.V., www.bau-umwelt.com,
07/2014

GaBi 6 2012

GaBi 6: Software and database for life cycle
engineering. LBP, University of Stuttgart and PE
INTERNATIONAL AG, Leinfelden-Echterdingen, 2012.

GaBi 6 2012B

GaBi 6: Documentation of GaBi6-Datasets for life cycle
engineering. LBP University of Stuttgart and PE
INTERNATIONAL AG, 2012.
<http://documentation.gabi-software.com/>

DIN 4108-10

DIN 4108-00 (2004-09): Thermal insulation and energy
economy in buildings - Part 10: Application-related
requirements for thermal insulation materials - Factory
made products

EN 14064 - Part1

EN 14064:2010 Thermal insulation products for
buildings - In-situ formed loosefill mineral wool
products - Part 1: Specification for the loosefill
products before installation

EN 14064 - Part2

EN 14064:2010 Thermal insulation products for
buildings - In-situ formed loosefill mineral wool
products - Part 2: Specification for the installed
products

EN 12667

EN 12667: 2001 Thermal performance of building
materials and products - Determination of thermal
resistance by means of guarded hot plate and heat
flow meter methods - Products of high and medium
thermal resistance

EN 1602

EN 1602: 2013 Thermal insulating products for building
applications - Determination of the apparent density

EN 29053

EN 29053: 1993 Acoustics; materials for acoustical
applications; determination of airflow resistance

EN 1609

EN 1609: 2013 Thermal insulating products for building
applications - Determination of short term water
absorption by partial immersion

EN 12087

EN 12087: 2013 Thermal insulating products for
building applications - Determination of long term water
absorption by immersion

EN 13501-1

EN 13501-1: 2009 Fire classification of construction
products and building elements - Part 1: Classification
using test data from reaction to fire tests

ISO 10456

ISO 10456: 2007 Building materials and products -
Hygrothermal properties - Tabulated design values and
procedures for determining declared and design
thermal values

DIN 4102 / T17

DIN 4102 / T17: 1990 Fire behaviour of building
materials and elements; determination of melting point
of mineral fibre insulating materials; concepts,
requirements and testing

Regulation (EU) No 305/2011/

Regulation (EU) No 305/2011/ laying down
harmonized conditions for the marketing of
construction products and repealing Council Directive
89/106/EEC .

Regulation (EC) No 765/2008

Regulation (EC) No 765/2008 setting out the
requirements for accreditation and market surveillance
relating to the marketing of products and repealing
Regulation (EEC) No 339/93

Zulassung Z-23. 15-1461

Zulassung Z-23. 15-1461 Building inspection approval
issued by the Deutsches Institut für Bautechnik (DIBt),
Berlin. Wärmedämmstoffe aus Mineralwolle (MW)
nach DIN EN 13162:2009-02.



Publisher

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com



Programme holder

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 - 3087748 - 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com



Author of the Life Cycle Assessment

Université de Liège
Allée du 6 Aout B6
4000 Sart-Tilman (Liège)
Belgium

Tel +3243663547
Fax +3243664435
Mail saicha.gerbinet@ulg.ac.be
Web www.chimapp.ulg.ac.be



PE International
Hauptstrasse 111
70771 Leinfelden-Echterdingen
Germany

Tel +497113418170
Fax +4971134181725
Mail info@pe-international.com
Web www.pe-international.com



Owner of the Declaration

Knauf Insulation
Rue E. Francqui 7
1435 Mont-Saint-Guibert
Belgium

Tel +3210488458
Fax +3210488474
Mail sustainability@knaufinsulation.com
m
Web www.knaufinsulation.com