



Rock Mineral Wool Insulation Products



# SAFETY DATA SHEET

### Rock Mineral Wool Products

According to Regulation (EC) No 1907/2006, Annex II, as amended., Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

- Knauf Insulation Rock mineral wool.
- Product name Rock Mineral Wool Products

Product number KI\_DP\_501

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesThermal, fire and/or acoustic insulation for use in technical & industrial applications, building<br/>construction and in other similar applications.

### 1.3. Details of the supplier of the safety data sheet

Supplier	Knauf Insulation Am Bahnhof 97346 Iphofen Germany Tel: +386 (0) 4 5114 104 oem@knaufinsulation.com www.oem.knaufinsulation.com
Region	UK

### 1.4. Emergency telephone number

Emergency telephone	Tel: +44 (0) 1744 766 666	
	(Monday - Friday, 08:00 hrs - 17:00 hrs)	

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (EC 1272/2008)

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements

NC Not Classified

### The following sentences and pictograms are printed on packaging

The mechanical effect of fibres in contact with skin may cause temporary itching.











http://www.knaufinsulation.com/comfort-and-handling

#### 2.3. Other hazards

Specific hazards

Not applicable.

SECTION 3: Composition	/information on ingredients	
3.2. Mixtures		
Rock Mineral Wool		90 - 100%
CAS number: —	EC number: 926-099-9	REACH registration number: 01- 2119472313-44-XXXX
EU index number: 650-0 Ingredient notes:(1)	16-00-2	
Classification Not Classified		
Thermo set, inert polyme formaldehyde resin	er based on cured phenol	0 - 10%
CAS number: —		
Classification Not Classified		
The Full Text for all R-Ph	ases and Hazard Statements are Displayed in Se	ection 16.
Ingredient notes	oxide and alkali earth oxide (Na <sub>2</sub> O+K <sub>2</sub> O+C	cate) fibres with random orientation with alkaline aO+MgO+BaO) content greater than 18% by Q of regulation n° 1272/2008 and therefore not
	CAS: Chemical Abstracts Service.	

Other information

Possible facing materials: glass veil, or polyester mat or aluminium or Kraft paper, wired mats.

SECTION	4: First aid measures	;
---------	-----------------------	---

SECTION 4: First aid measure	15
4.1. Description of first aid me	asures
Inhalation	Remove from exposure. Rinse the throat and clear dust from airways.
Ingestion	Drink plenty of water if accidentally ingested.
Skin contact	If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.
Eye contact	Rinse abundantly with water for at least 15 minutes.
4.2. Most important symptoms	and effects, both acute and delayed
General information	The mechanical effect of fibres in contact with skin may cause temporary itching.
4.3. Indication of any immedia	te medical attention and special treatment needed
General information	If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.
SECTION 5: Firefighting meas	sures
5.1. Extinguishing media	
Suitable extinguishing media	Water, foam, carbon dioxide (CO2), and dry powder.
5.2. Special hazards arising fro	om the substance or mixture
General information	Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.
5.3. Advice for firefighters	
General information	In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required.
SECTION 6: Accidental release	ie measures
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions	In case of presence of high concentrations of dust, use the same personal protective equipment as mentioned in section 8.
6.2. Environmental precaution	<u>s</u>
Environmental precautions	Not relevant.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up	Vacuum cleaner or dampen down with water spray prior to brushing up.
6.4. Reference to other section	<u>15</u>
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

7.1. Precautions for safe ha	ndling
Usage precautions	No specific measures. Cut using a knife, do not use a saw or use power tools. Avoid unnecessary handling of unwrapped product. Provide adequate ventilation.
7.2. Conditions for safe stor	age, including any incompatibilities
Storage precautions	To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended. Delivered packed in polyethylene film and or on wooden pallets.
Incompatible materials	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
7.3. Specific end use(s)	
Specific end use(s)	Thermal, fire and/or acoustic insulation for use in technical & industrial applications, building construction and in other similar applications.

### SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

### **Rock Mineral Wool**

Long-term exposure limit (8-hour TWA): WEL 2 fibres/ml 5 mg/m<sup>3</sup> Machine-made mineral fibre (except for refractory ceramic fibres and special purpose fibres)

WEL = Workplace Exposure Limit

None at European level, refer to member state guidelines and legislation.

### 8.2. Exposure controls

Appropriate engineering controls	No specific measures.
Eye/face protection	Use goggles especially if working above shoulders. Eye protection according to EN 166 is advised.
Hand protection	Use gloves to avoid itching in conformity with EN 388.
Other skin and body protection	Cover exposed skin.
Hygiene measures	After contact, wash hands with cold water and soap.
Respiratory protection	Wearing a face mask type in accordance with EN 149 FFP1 is recommended when using products in confined atmosphere or during operations which can generate emission of any dust.

SECTION 9: Physical and Che	emical Properties
9.1. Information on basic phys	ical and chemical properties
Appearance	Solid. Roll or panel.
Colour	Ochre.
Odour	Not relevant.
Odour threshold	No data available.
рН	Not relevant.
Melting point	Fibre melting point > 1000 °C according to DIN 4102-17.
Initial boiling point and range	Not relevant.
Flash point	Not relevant.
Evaporation rate	Not relevant.
Flammability (solid, gas)	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Vapour pressure	Not relevant.
Vapour density	Not relevant.
Relative density	30 - 250 kg/m³
Solubility(ies)	Generally chemically inert and insoluble in water.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	Not relevant.
Explosive properties	Not relevant.
Oxidising properties	Not relevant.
9.2. Other information	
Nominal diameter of fibres	3 - 7 μm
Length weight geometric mean diameter less 2 standard errors	≈ 6 µm
Orientation of fibres	Random

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Reactivity	None.	
10.2. Chemical stability		
Stability	Binder will decompose above 200°C.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	None in normal conditions of use.	
10.4. Conditions to avoid		
Conditions to avoid	Heating above 200 °C.	
10.5. Incompatible materials		
Materials to avoid	None.	
10.6. Hazardous decompositi	on products	
Hazardous decomposition products	None in normal conditions of use. Decomposition of binder above 200°C may produce carbon dioxide and some trace gases. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied.	
SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Toxicological effects	The mechanical effect of fibres in contact with skin may cause temporary itching.	
General information	Classification not applicable for this product; in accordance with European Regulation 1272/2008, note Q.	

SECTION 12: Ecological Information	
12.1. Toxicity	
Toxicity	This product is not ecotoxic to air, water or soil, by composition.
12.2. Persistence and degrada	ıbility
Persistence and degradability	Inert inorganic product with Thermo set, inert polymer based on cured phenol formaldehyde resins; 0 - 10%
12.3. Bioaccumulative potentia	<u>u</u>
Bioaccumulative potential	Will not bioaccumulate.
12.4. Mobility in soil	
Mobility	Not considered mobile. Less than 1% leachable organic carbon if landfilled.
12.5. Results of PBT and vPvE	3 assessment
Results of PBT and vPvB assessment	Not relevant.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal consid	erations
13.1. Waste treatment method	<u>S</u>
General information	[17 06 04] Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Disposal methods	Dispose of in accordance with regulations and procedures in force in country of use or disposal.

### **SECTION 14: Transport information**

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

#### SECTION 15: Regulatory information

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18
-	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of
	Chemicals (REACH) (as amended).
	Commission Regulation (EU) No 2015/830 of 28 May 2015.
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
	The European Regulation on Chemicals No 1907/2006, Registration, Evaluation,
	Authorisation of Chemicals (REACH) enacted on June 1st 2007 requires the provision of
	Safety Data Sheet (SDS) for hazardous substances and mixtures / preparations.
	Knauf Insulation mineral wool products (panels, batts or rolls), are defined as articles under
	REACH and therefore a Safety Data Sheet for these products is not a legal requirement.
	In accordance with industry practice and voluntary commitments, Knauf Insulation has
	decided to continue to provide its customers with the appropriate information for the purpos
	of assuring safe handling and use of mineral wool throughout the product life.

### Not relevant. **SECTION 16: Other information** Abbreviations and acronyms ADR: European Agreement concerning the International Carriage of Dangerous Goods by used in the safety data sheet Road. ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. IARC: International Agency for Research on Cancer. IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods. MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. PBT: Persistent, Bioaccumulative and Toxic substance. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. UN: United Nations. vPvB: Very Persistent and Very Bioaccumulative.

General information All products manufactured by Knauf Insulation are made of non-classified fibres and are certified by EUCEB.

EUCEB, European Certification Board of Mineral Wool Products - www.euceb.org. The EUCEB trademark certifies that the manufactured fibres have a chemical composition within the ranges of exonerated reference fibres, which have been tested in accordance with European protocols and have been shown to be in conformity with Note Q, exoneration criteria for carcinogenicity, of the Regulation (EC) 1272/2008.

The mineral wool producers commit to EUCEB to:

supply sampling and analysis reports established by laboratories recognized by EUCEB, proving that the fibres comply with one of the four criteria of exoneration described in Note Q,
be controlled, twice per year, of each production unit by an independent third party recognized by EUCEB (sampling and conformity to the initial chemical composition),
put in place procedures of internal self-control in each production unit.

Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

### Further information can be obtained from

www.euceb.org

www.knaufinsulation.com



Revision comments	New document format
Revision date	30/09/2016
Revision	4.0
Supersedes date	04/07/2016
SDS number	KI_DP_501
OEM Product Families	PBE, DRS, DAP, CHM, TSP, RSB, MCH, CNF, CTL, WWC, AUT, HTC, SPA
Other information	In 2001, the International Agency for Research on Cancer (IARC) reclassified rock mineral wool fibres from Group 2B (possibly carcinogenic) to Group 3 «agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, http://monographs.iarc.fr/)

This Safety Data Sheet / Product Data Sheet does not constitute a workplace assessment.

Information contained in this document represents the state of our knowledge regarding this product as of the date of issue of the document. Attention of users is drawn to possible risks taken when the product is used for other applications than the ones it has been designed for.