

EARTHWOOL®

the feel good glasswool insulation

DriTherm®: Brick Cavity Wall Insulation

Repels summer heat. Retains winter warmth.

DriTherm Cavity slab is made using recycled glass and with ECOSE® Technology, a revolutionary binder that contains no added formaldehyde, phenols or acrylics and provides a tried and tested solution for masonry walls.

Full fill



Fully fills the cavity to ensure high thermal performance. Product is also flexible to fit around wall imperfections.



Fire Performance

DriTherm Cavity Slab is non-combustible and classified as Euroclass A1 to BS EN ISO 13501-1 – the highest possible.

Thermal Performance



High thermal performance with a material R-Value of 1.4 m²K/W.



Water Resistant

DriTherm Cavity Slab contains a water repellent additive to ensure that no liquid water is able to pass through the product and reach the inner leaf of masonry.

Sustainability



DriTherm Cavity Slabs are manufactured with ECOSE® Technology which reduces embodied energy and delivers superior environmental sustainability compared to traditional glasswool products.



BCA Compliant

DriTherm Cavity Slab is CodeMark certified, demonstrating that it meets the Building Code of Australia (BCA) requirements for the installation of insulation in a masonry brick cavity. Legislation requires building control authorities to accept CodeMark certified products and therefore gives contractors and specifiers absolute confidence in the products use.



50 Year Warranty

DriTherm Cavity Slab is guaranteed for 50 years to resist the passage of water from the outer to the inner leaf.

DriTherm	Fineline	Thickness (mm)	R-Value (m ² K/W)	Length (mm)	Width (mm)	Area per pack (m ²)
	0811072	50	1.4	1100	600	5.3

For more information visit www.knaufinsulation.com.au

