

# **DUCT LINER ROLL**

### November 2018



# **APPLICATIONS**





### **DESCRIPTION**

Atmosphere™ Duct Liner Roll is a flexible, mat-faced insulation for HVAC lining, bonded with ECOSE® Technology. It is faced with a tightly bonded mat to give the airstream a smooth, tough surface, resisting damage during installation and operation.

# **PERFORMANCE**

-				_ •	
Δ	•	^		٠i	•

Noise reduction coefficient: 0.70 NRC

Fire

Classification: Developed when tested in accordance with ASTM E84

**Service Temperature** 

Operating temperature:

Up to 120 C

**Air Velocity** 

Maximum 1800 mpm, tested to 4500 mpm

Does not exceed 25 Flame Spread, 50 Smoke

### **BENEFITS**

- Low thermal conductivity
- ✓ Fire-resistant, non-corrosive and durable
- Tough, tightly bonded mat facing
- Excellent sound absorption
- Lowers operating costs
- Greatly reduces noise from fans and mechanical equipment as well as cross-talk and air movement
- ✓ Low emitting for indoor air quality considerations

# **SPECIFICATIONS**

Facing	Thickness (mm)	<b>Length</b> (m)	Width (mm)	Area per pack (m²)	Thermal Conductivity (W/m.K)	R Value $(m^2.K/W))$	<b>Density</b> kg /m³	<b>Rolls</b> per pack
WGF	25	15.5	1200	18.6	0.035	0.69	24	1

All dimensions are nominal.

# SOUND ABSORPTION COEFFICIENTS (ASTM C423 - MOUNTING TYPE A AS PER ASTM E795)

<b>Density</b> (kg/m³)	Thickness (mm)	Absorption Coefficient of one-third octave Band center Frequency Hz						
		125	250	500	1000	2000	4000	NRC
24	25	0.18	0.36	0.59	0.86	0.95	0.9	0.7

# **CERTIFICATION**















# **DUCT LINER ROLL**

**November 2018** 

# **ADDITIONAL INFORMATION**

### **Application**

Specifically designed as an interior insulation material for sheet metal ducts used in heating, ventilating and air conditioning. Provides an optimum combination of efficient sound absorption, low thermal conductivity and minimal airstream surface friction.

#### Standards

Atmosphere™ Duct Liner Roll is manufactured in accordance with BS EN 13162, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

### Certification

Atmosphere™ Duct Liner Roll are certified under ASTM E84, DCL Product Conformity, EUCEB for conformity of fibres produced with the requirements of Note Q of the Regulation (EC) No 1272.2008 of EP and EC, EUROFINS Indoor Air Quality Gold, SASO Product Conformity.

### **Durability**

Atmosphere<sup>TM</sup> Duct Liner Roll is adourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### **Environmental**

Duct Liner Roll Ultimate represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

### **Indoor Air Quality**

Atmosphere™ Duct Liner Roll represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

### **Water Vapour Sorption**

Atmosphere™ Duct Liner has a sorption less than 3% by its weight as per ASTM C 1104.

### Handling and storage

Atmosphere™ Duct Liner Roll is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied enclosed in polythene which is designed for short term protection only. For longer term protection on site, the product should be stored either indoors, or under cover and off the ground. Atmosphere™ Duct Liner Roll should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

### **Knauf Insulation LLC**

Mussaffah ICAD 1, P.O.Box 34332, Abu Dhabi, United Arab Emirates

Customer Service: +971 2 551 2453 Technical Support & Marketing: +971 2 551 2453 Email: technicalsupport@kei.ae

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

