

## DUCT WRAP ROLL ULTIMATE

November 2018

### APPLICATIONS



### DESCRIPTION

Atmosphere™ Duct Wrap Roll Ultimate with ECOSE® Technology is a thermal and acoustical insulation blanket for HVAC wrapping, made from highly resilient, inorganic glass mineral wool bonded by ECOSE Technology. It is available with a foil-scrim-kraft (FSK) jacket.

### PERFORMANCE

#### Thermal

Conductivity: 0.033 W/mK at 25 C

#### Fire

Classification: Does not exceed 25 Flame Spread, 50 Smoke  
Developed when tested in accordance with ASTM E84.

#### Service Temperature

Duct Wrap Roll - up to 230°C  
Operating temperature: Aluminium Facing - up to 80°C

### BENEFITS

- ✓ Low "k" factor significantly reduces heat gain or loss when applied with proper compression
- ✓ Flexible and lightweight
- ✓ Excellent acoustical properties
- ✓ Energy conservation, which lowers operating costs
- ✓ Allow faster installation, lower labor costs
- ✓ Sound reduction through the duct wall
- ✓ Assured condensation control when installed at proper thickness using FSK or Aluglass facings

### SPECIFICATIONS

Facing	Thickness (mm)	Length (m)	Width (mm)	Area per pack (m²)	Thermal Conductivity (W/m.K)	R Value (m².K/W)	Density kg/m³	Rolls per pack
FSK	50	7.5	1200	9	0.035	1.52	32	1
Aluglass	50	7.5	1200	9	0.033	1.52	32	1
FSK	25	15	1200	18	0.035	0.79	32	1
Aluglass	25	15	1200	18	0.033	0.79	32	1

All dimensions are nominal.

### CERTIFICATION



## DUCT WRAP ROLL ULTIMATE

November 2018

### ADDITIONAL INFORMATION

#### Application

Atmosphere™ Duct Wrap Roll Ultimate is used as external insulation on commercial or residential heating or air conditioning ducts. It is suitable for the exterior of rectangular or round sheet metal ducts and spaces or surfaces where temperature and condensation must be controlled.

#### Standards

Atmosphere™ Duct Wrap Roll Ultimate is manufactured in accordance with BS EN 13162, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

#### Certification

Atmosphere™ Duct Wrap Roll Ultimate are certified under UL 723, DCL Product Conformity, EUCB for conformity of fibres produced with the requirements of Note Q of the Regulation (EC) No 1272.2008 of EP and EC, EUROFINS Indoor Air Quality Gold, SASO Product Conformity.

#### Durability

Atmosphere™ Duct Wrap Roll Ultimate is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Environmental

Atmosphere™ Duct Wrap Roll Ultimate represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

#### Indoor Air Quality

The new Atmosphere line from Knauf Insulation aims to offer a healthier series of air handling products for improved indoor air quality. Using ECOSE technology, it is the only such insulation available that's free of both formaldehyde and Decabromodiphenyl ether (decaBDE) and the only insulation to receive the coveted Eurofins Indoor Air Quality Gold Standard.

#### Water Vapour Transmission

Atmosphere™ Duct Wrap Roll Ultimate (FSK) have a maximum water vapor permeance of 0.02 perms (FSK) and 0 perms (Aluglass) as per ASTM E96.

#### Handling and storage

Atmosphere™ Duct Wrap Roll Ultimate is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied enclosed in polythene which is designed for short term protection only. For longer term protection on site, the product should be stored either indoors, or under cover and off the ground. Atmosphere™ Duct Wrap Roll Ultimate should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

#### Knauf Insulation LLC

Mussaffah ICAD 1, P.O.Box 34332,  
Abu Dhabi, United Arab Emirates

Customer Service: +971 2 551 2453    Technical Support & Marketing: +971 2 551 2453    Email: [technicalsupport@kei.ae](mailto:technicalsupport@kei.ae)

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE3482DAT - V1118

challenge.  
create.  
care.