


THERMO-TEK RL ECO ALL



January 2021

APPLICATION RANGE



DESCRIPTION

Thermo-teK RL ECO ALL is a mineral wool roll with formaldehyde-free binder and fibre glass reinforced, tear-resistant aluminium foil on one side (with overlap along the roll).

TECHNICAL DATA

Maximum service temperature	60 °C (EN 14706)
Reaction to fire	A2-s1, d0 (EN 13501-1)
Density	ca. 25 kg/m ³ (EN 1602)
Declaration of performance*	http://dopki.com/T4220MP

* for detailed information on DoP please check the product label

Description	Sign	Description/data					Unit	Norm
Thermal conductivity depending on temperature	9	10	20	40	60		°C	EN 12667
	λ	0.034	0.036	0.040	0.044		W/(mK)	
Water vapour diffusion equivalent air layer thickness	S _d	≥ 200					m	EN 12086
Designation code	-	MW-EN14303-T2-ST(+)-60					-	EN 14303

Declared material properties are obtained in the production process and ensured by the factory production control in accordance with the European Standard at the time of manufacture. Observing storage and handling guidelines will maintain performance within published tolerances.

CERTIFICATE



challenge.
create.
care.

THERMO-TEK RL ECO ALL



January 2021

ADDITIONAL INFORMATION

Application

The product is recommended for thermal, fire and sound insulation of the defined applications within technical insulation, **where overlapping during the installation is required**. Pipe lines, Valves & flanges, Air duct insulation (rectangular and circular).

Handling

Knauf Insulation products are easy to handle and easy to install. They are supplied in suitable packaging materials to balance necessary transport protection with sustainable recycling options. Packaging is not designed for long-term storage or exposure to harsh weather conditions. Further product information is mentioned on every pack.

Storage

For longer-term protection on site we recommend storing the product either indoors or alternatively under a roof cover and off the ground. If covered storage is not available, products can be stored outside (open-air-storage) if placed off the ground (keep palletized) and covered with plastic hood (foil), for a maximum of up to 6 months from the date of delivery. Outdoor storage is not recommended during particularly humid months with large fluctuations in temperature.

Standard formats*

Thickness	25 mm, 50 mm
Width	1 200 mm

* Other dimensions on request.



Knauf Insulation mineral wool products with ECOSE® Technology benefit from a formaldehyde-free binder made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE® Technology contain no dye or artificial colours – the colour is completely natural.

ISO STANDARDS

Knauf Insulation products are produced according to four of the most important International Management Standards for sustainability ISO 9001 (Quality Management), ISO 14001 (Environmental Management), ISO 50001 (Energy Management) and ISO 45001 (Health and Safety Management), all certified by Tüv Nord.

Knauf Insulation Sprl

Rue de Maestricht 95, 4600 Visé
Belgium

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work presented in this document is not permitted. Extreme caution was taken in assembling the information, texts and illustrations in this document. Nevertheless, errors cannot be entirely ruled out. The publisher and editors assume no legal responsibility or any liability whatsoever for any incorrect information or any consequences thereof. The publisher and editors are grateful for any suggestions for improvement as well as the identification of any errors.