

ROCKSILK® RAINSCREEN SLAB INSTALLATION GUIDE - CLADDING OUTER LEAF



WHAT YOU NEED TO KNOW

CONTENTS

	Page
Safety considerations	3
Typical Rainscreen Systems	4
BBA Certified Solutions	6
Placement	7
Installation Sequence	11
Cutting	14
Fixings	15
Detailing Considerations	19
Maintenance	20

SAFETY CONSIDERATIONS


STORAGE

Rocksilk® RainScreen Slab should be stored properly and handled in such a way as to ensure that the product remains clean and undamaged.

The shrink-wrapped pallets used for the supply of Rocksilk® RainScreen Slab are designed for short-term protection only. For longer term protection on site, the product should either be stored indoors or under cover and off the ground. Rocksilk® RainScreen Slab should not be left permanently exposed to the elements.

If the main hood is removed or damaged, the remaining packs should be kept under cover indoors or protected from the elements by a weatherproof cover. In coastal locations where weather is more extreme and bird damage is more common, use additional covering or store indoors.

The product must be protected from prolonged exposure to sunlight, and stored dry and flat.




✓ Slabs protected from weathering potential

HANDLING

Rocksilk® RainScreen Slab is light and easy to handle; care should be exercised to avoid crushing their edges or corners. If damaged, the product should be discarded. Damaged, contaminated or wet product must not be used.

During construction exposed areas of slabs should always be covered at the end of a day's work or in heavy rain. Polyethylene covers should be used to provide protection and prevent work from becoming saturated.



✗ Slabs exposed to the elements

SAFETY EQUIPMENT AND TOOLS

It is recommended that the following Personal Protective Equipment should be used while handling the product:

PPE: Dust mask (FFP1 minimum), gloves, safety glasses


Tools: Knife or fine-toothed saw, tape measure

It is recommended that dust masks, gloves and long-sleeved clothing should be worn during cutting and handling of the product.




TYPICAL RAINSCREEN SYSTEMS

MASONRY SUBSTRATE INSTALLATION




STEEL FRAME RAIL INSTALLATION




TYPICAL RAINSCREEN SYSTEMS

PRECAST CONCRETE INSTALLATION



TIMBER FRAME INSTALLATION




Note: Breather membrane can be used although not shown


BBA CERTIFIED SOLUTIONS




STEEL FRAME
SINGLE LAYER




STEEL FRAME
DOUBLE LAYER




TIMBER FRAME




MASONRY



REINFORCED
CONCRETE



CROSS LAMINATED
TIMBER




PLACEMENT

JOINTS BETWEEN SLABS SHOULD BE STAGGERED

Joints between slabs should be staggered by a minimum of 100mm and coincidental joints should be avoided.

? **To avoid gaps between slabs.**



Note: Fixings as per guidance given in section 6.3 BR 135 3rd Edition

PLACEMENT

DOUBLE-FACED


IT DOESN'T MATTER WHICH WAY ROUND IT IS INSTALLED

Installed with either face in continuous intimate contact with the substrate without affecting its durability or thermal properties.

SLABS TO BE IN CONTACT WITH EACH OTHER

Installed such that they are tightly butted together at joints and joints staggered by a minimum of 100mm.


? **To avoid coincidental joints and maintain thermal, acoustic and weather performance.**



INTIMATE CONTACT WITH SUBSTRATE

Rocksilk® RainScreen Slab should be in intimate contact with the building substrate. The nature of the insulation material lends itself to accommodate any irregularities in the surface of the substrate.

? **Creating a snug fit between the slabs and the wall reduces the chance for air gaps and ensures thermal efficiency.**




PLACEMENT

COMPRESSION FIT INTO PLACE

Rocksilk® RainScreen Slab should be cut slightly oversize and compression fitted into place.


? To create a snug fit between slabs, reducing the chance for air gaps and ensuring thermal efficiency.



MAINTAIN A VENTILATED CAVITY

Make sure a ventilated cavity remains between the insulation and the external cladding. NHBC guidance states a requirement for 50mm when open joints are used and 38mm when baffled or labyrinth joints are used.

- ✓ Cavity of 50mm
- ✗ Cavity below 50mm unless baffled or labyrinth joints used




PLACEMENT

ROCKSILK® RAINSCREEN SLAB BELOW DAMP PROOF COURSE

Rocksilk® RainScreen Slab does not absorb water by capillary action and may therefore be used in situations where it bridges the dpc's of the inner and outer leaf.

? To simplify installation




INSTALLATION SEQUENCE

RAINSCREEN CLADDING OUTER LEAF DUAL LAYERING

SFS or timber substrate

Option 1

1. The first row should be installed in line with edges of the slab being in the centre of the studs.
2. Should it be necessary, the first row of slabs can be fixed with fixings through the centre of the slabs directly into the sheathing board for additional support
3. The next layer of Rocksilk® RainScreen Slab should be installed in the opposite orientation. These slabs should be fixed in position using one stainless steel fixing in the centre of the slab through to the stud, and either stainless steel or plastic washers at horizontal slab joints. Where slabs are installed over cladding brackets care should be taken to ensure that they are tightly fitted, ensuring optimum thermal performance.



- KEY:
- SFS or timber studs
 - First layer of Rocksilk® RainScreen Slab
 - Second layer of Rocksilk® RainScreen Slab
 - Fixings


INSTALLATION SEQUENCE

RAINSCREEN CLADDING OUTER LEAF DUAL LAYERING

SFS or timber substrate

Option 2

1. The first row should be installed in line with edges of the slab being in the centre of the studs.
2. Should it be necessary, the first row of slabs can be fixed with fixings through the centre of the slabs directly into the CP board for additional support
3. The next layer of Rocksilk® RainScreen Slab should be installed in the same orientation staggered by 300mm to the first layer so that the slabs run evenly through the centre of the stud. Stainless steel fixings should then be installed through the centre of each slab with either stainless steel or plastic washers used for additional support at vertical slab joints.



- KEY:
- SFS or timber studs
 - First layer of Rocksilk® RainScreen Slab
 - Second layer of Rocksilk® RainScreen Slab
 - Fixings


INSTALLATION SEQUENCE

RAINSCREEN CLADDING OUTER LEAF DUAL LAYERING

Masonry or concrete substrate

Either of the SFS or timber substrate installation techniques can be used on a masonry or concrete substrate, along with the further option below. The key design consideration is to ensure at least one stainless steel fixing goes through each of the second layer of slabs.

1. The first 2 rows should be installed in a landscape or portrait orientation
2. Should it be necessary, the first two rows of slabs can be fixed with fixings through the centre of the slabs directly into the concrete/blockwork for additional support
3. The next layer of Rocksilk® RainScreen Slab should be installed in the opposite orientation staggered by 600mm to the first layer of Rocksilk® RainScreen Slab. The slabs are then fixed in position using one stainless steel washer in the centre of the slab through to the concrete/blockwork and either metal or plastic washers at horizontal slab joints, directly into the concrete/blockwork.



KEY: ■ Blockwork or concrete panel
■ First layer of Rocksilk® RainScreen Slab
■ Second layer of Rocksilk® RainScreen Slab

CUTTING


CUT NEATLY AROUND PENETRATIONS AND CONSTRUCTION DETAILS - CUT OVERSIZE BY 5MM

Cut neatly around penetrations and construction details using a sharp bladed knife or insulation saw. When cutting around penetrations, cut oversize by 5mm to allow some local compression of the slab around the feature to ensure a snug fit.

? **To maximise thermal performance.**

✓ Leave 5mm overcut

✗ Cut directly up to penetrations



CUT NEATLY WITH A SHARP INSULATION SAW/KNIFE

Cut neatly with a fine serrated saw or a large bladed knife.

? **Gives a factory quality cut and prevents tearing**

✓ Use insulation saw or knife

✗ Rip using coarse blade




AREAS THAT CANNOT ACCEPT FULL SLAB SHOULD USE A SLAB SECTION

Areas of insulation that do not require a full slab (aside from corners where a full slab must be used) can be filled using a slab section, where the section is cut slightly oversize to give a snug fit and fixed at 600mm intervals in the centre of the section. Each slab section should receive one non-combustible fixing and washer in addition to any other fixings as required to maintain continuity of the insulation.

✓ Slab cut and snug fit

✗ Loose fit for cut slab section



FIXINGS



POLYPROPYLENE AND STAINLESS STEEL WASHERS

Fix using all stainless steel or a combination of stainless steel and polypropylene washers in accordance with the detailed fixing pattern.

✓ **Min 1 stainless steel washer per slab**

✗ **All plastic washers**

WASHER:  Stainless Steel  Polypropylene



Stainless steel washers for fire safety

Stainless steel washers retain their strength in the event of a fire

Fixing pattern


For fire safety and retention of insulation slab

DON'T OVERTIGHTEN MECHANICAL FIXINGS

Ensure that mechanical fixings are not overtightened; surface compression of the product is not recommended.



This compromises the thermal performance and can lead to localised moisture pooling.



FIXINGS

FIXINGS TO USE

Exact fixings will depend on the type of substrate. Suitable Fixing Manufacturers:

Hilti: 0800 886100

Ejot: 01977 687040

Fischer: 01491 827900

Fixfast: 0800 304 7616

Consult fixing manufacturer guidance. A minimum of one non-combustible fixing should be provided for each slab and must be provided in addition to other fixings. Fixings should be corrosion resistant and provide satisfactory in-service performance for the design life of the building.


Ensure fixing equipment does not damage the product during the fixing process e.g. drill chucks.

CORNER DETAILS - ADDITIONAL FIXINGS

Rocksilk® RainScreen Slab should be installed using additional fixings around corner details, where fixings are added to each slab corner such that it is fixed firmly to the super structure.

Rocksilk®
RainScreen Slab

Zone for
additional fixings



WASHER MINIMUM DIAMETER OF 70MM


When installing the fixings to retain the insulation, a washer with a minimum diameter of 70mm must be used to ensure optimum strength of fixing between Rocksilk® RainScreen Slab and substrate.



Washers 70mm or ABOVE



Washers BELOW 70mm





FIXINGS

WIND LOADING

Rocksilk® RainScreen Slab has been tested by BRE to *BRE digest 346 The assessment of wind loads – part 7: Wind speeds for serviceability and fatigue assessments*. The slab withstood the applied dynamic wind loading at a maximum design pressure of -3600Pa, or 76m/s as calculated to BS EN 1991 without showing signs of damage or distress, maintaining its structural integrity.

Wind load performance of the overall system is generally limited not only by the integrity of the insulation, but also by the material strength of either the structure or the anchor. It is necessary to ensure that the performance of both the substrate and the anchor are greater than that of the insulation.


For accurate data on fixings or substrates such as Concrete, Structural Framing Systems, or Cross Laminated Timber, please consult individual manufacturers.

FIXINGS

WHERE ROCKSILK® RAINSCREEN SLAB HAS BEEN INCLUDED IN COMPLETE SYSTEM TEST

Some system manufacturers have included Rocksilk® RainScreen Slab in complete system tests for fire and acoustic performance. In principle, the fixing detail - including the location of the fixings - should be in line with both the system holder's requirements and those detailed in this guide. If in doubt, please consult Knauf Insulation Technical Services.

Knauf Insulation Rocksilk® RainScreen Slab can be combined with Knauf UK ThroughWall Systems, providing the unique advantage of being able to specify the façade infill through to the internal partitions. This combination has been tested for fire resistance of 120 minutes when exposed to fire on the inside and outside (Rocksilk® RainScreen Slab face) of the structure. The installation specifications used in these tests require the fixings for retaining the mineral wool to be directly into the SFS studs.



This is an illustrative example of the Knauf UK ThroughWall System only, other build-ups are suitable.


DETAILING CONSIDERATIONS

WINDOW DETAILS

Cut slabs to fit neatly around window details. Additional fixings and washers may be required to firmly retain the slabs and ensure continuity of the insulation layer. Fixings should have a minimum of one non-combustible (metal) washer per cut slab in addition to other fixings.

Each slab should contain at least one stainless steel washer.

WASHER:  Stainless Steel  Polypropylene



INSTALLATION AROUND BRACKET PENETRATIONS

Product should be offered up to penetration, applying sufficient pressure to allow a small indent to be made in the product. Indent should be made on the face that will come into contact with the substrate when the product is installed.

Cut a slot in the product with an insulation saw or large bladed knife. Install product over the bracket taking care not to damage the external face of the slab. Ensure that the product is in intimate contact with neighbouring slabs. Secure the slab to the wall substrate with mechanical fixings in accordance with the design specification.

? Ensures a tight fit of slabs around penetrations, ensuring maximum thermal efficiency.



FIRE BARRIERS

Cavity barriers should be installed to meet the requirements of *Approved Document B* - England and Wales, *Handbook Section 2* - Scotland and *Technical Booklet E* - Northern Ireland.

MAINTENANCE

ROLLING FRONT - BEST PRACTICE

Rocksilk® RainScreen Slab is designed with a water-repellent additive to be weather resistant, however Rocksilk® RainScreen Slab should be covered up with the cladding as work proceeds, on the basis of an advancing front.

- ✓ Cladding should be immediately installed to cover Rocksilk® RainScreen Slab to reduce weathering.




PARAPET / ROOF LEVEL PROTECTION DURING INSTALLATION

The top edge of the slabs should be covered and any run off water directed away from running down the face of the slabs.

Breather membrane


Rocksilk® RainScreen Slab



CONSTRUCTION REPAIRS

In the event of small repairs being needed on site, Knauf Insulation recommends the replacement of full slabs wherever possible before installing the rainscreen panels.

- ✓ Full slab replacement after damage
- ✗ Small patched repair



SITE CHECK LIST ROCKSILK® RAINSCREEN SLAB

System type?	<input type="checkbox"/> Cladding	<input type="checkbox"/> Brickwork
Is the product plain or have a Black Glass Veil facing?	<input type="checkbox"/> Plain	<input type="checkbox"/> BGV
Has the product been stored off-ground and undercover?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Is there a breather membrane being used in the construction?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
- If yes, is the breather behind or in front of the insulation layer?	<input type="checkbox"/> Behind	<input type="checkbox"/> In front
Does the product being installed appear dry at the time of survey?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Has a single or double layer* of insulation been used?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
- If double-layered, have layers been staggered?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Has the product been mechanically damaged during installation?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Have the slabs been installed in "portrait" or "landscape" orientation?	<input type="checkbox"/> Portrait	<input type="checkbox"/> Landscape
Is the primary fixing washer a metal washer?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Is there a minimum of one metal washer on every slab?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Are the secondary fixing washers plastic or metal?	<input type="checkbox"/> Plastic	<input type="checkbox"/> Metal
Do washers have a minimum head diameter of 70mm?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Are all washers fixed so as to be flush with the surface of the slab?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Have additional fixings & washers been used around windows, corners or other features?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Are all slabs closely butted together such that there are no visible gaps between them?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Has the slab been cut to fit neatly over brackets?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Is the insulation bridged by another component of the construction other than the bracket?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Is there at least a 38mm residual ventilated cavity if cladding panel joints are baffled or 50mm residual ventilated cavity if open-jointed?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
If installed to parapet level, has the product been protected?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Have multiple cut pieces been avoided where possible?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Have slab joints been staggered by at least 100mm?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
What percentage of the installation is exposed to the elements?	<input type="text"/>	
What percentage of the installation of insulation has been completed?	<input type="text"/>	

*Rocksilk® RainScreen Slab BBA certified in single or double layer only.
This checklist is for on-site install guidance only, and is not a confirmation that Knauf Insulation has inspected or approved install of Rocksilk® RainScreen Slab during or after construction.

CONTACTS

Specification Team

knaufinsulation.co.uk/findmyrep

Technical Services Team

Tel: 01744 766 666

email: technical.uk@knaufinsulation.com

For more information please visit

knaufinsulation.co.uk/rainscreen-solutions



Knauf Insulation Ltd PO Box 10, Stafford Road, St.Helens, Merseyside, WA10 3NS. UK

For more information please visit knaufinsulation.co.uk

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, text and illustrations in this document. Nevertheless, errors cannot be completely ruled out. The publisher and editors cannot assume legal responsibility or any liability for incorrect information and consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out. For the most up-to-date document versions and product information, please always refer to our website.