

NaturBoard POD STANDARD

April 2020



with **ECOSE**
TECHNOLOGY

APPLICATIONS



PRODUCT DESCRIPTION

Insulation slab for floor structures

NaturBoard POD STANDARD is a compact rock mineral wool slab of stable density and belongs to the group of very hard products. The product is non-combustible, resistant to high temperatures, resistant to aging chemically neutral.

TECHNICAL CHARACTERISTICS

Declared coefficient of thermal conductivity λ_D	0.036 W/mK
Reaction to fire	A1 - non-combustible material
Water vapour diffusion resistance factor μ	~1
Air flow resistance AFR	>5 kPa·s/m ²
Short term water absorption W_p	≤1 kg/m ²
Long term water absorption W_{lp}	≤3 kg/m ²
Compressibility	CP4

DESIGNATION CODE: MW-EN 13162-A1-T6-WS-WL(P)-CP 4-AF 5

BENEFITS

- Non-combustible material A1
- Guaranteed protection from impact sounds
- Stability and compactness
- Resistance to aging
- The material meets health, safety and environmental requirements
- Simple and quick installation

DIMENSIONS AND PACKAGING

Thickness (mm)	Width (mm)	Length (mm)	pcs / packaging	m ² / packaging	packages / pallet	m ² / pallet	R Thermal resistance (m ² K/W)
20	600	1000	15	9,0	16	144,00	0,56
30	600	1000	10	6,0	16	96,00	0,83
40	600	1000	8	4,8	16	76,80	1,11
50	600	1000	6	3,60	16	57,60	1,39

CERTIFICATES



challenge.
create.
care.

NaturBoard POD STANDARD

April 2020

ADDITIONAL INFORMATION

Application

The product is intended for protection from impact sounds in floating floor structures, thermal insulation and fire protection. It is ideal for installation under wet screeds and for projected evenly distributed load up to 2kPa.

Packaging

The product NaturBoard POD STANDARD is delivered in PE heat-shrinking foil. The products must be stored in a dry place, indoors or under roof. In exceptional situations, the packages stored outdoors should be protected by watertight foil. The packages must not be placed directly on the ground.

Quality

NaturBoard POD STANDARD is certified to comply with standard EN 13162 as well as with the EUCB certificate which ensures that the product is biosoluble and not dangerous for health in accordance with European Directive 97\69\EC. Due to ECOSE Technology naturally based binder, it also possesses Eurofins Indoor Air Comfort Gold Certificate, regarding indoor Environmental Quality and Low-Emitting Materials.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation SA

10 Evripidou str.
176 74 Kallithea
Greece

sales.gr@knaufinsulation.com

Tel.: +30 211 710 7007

Fax.: +30 211 740 9480